



Ceiling Cutout: 6 9/16" (167 mm) Dia.

### Reflector Trim

- 8021 CCLW** Comfort Clear™, White Flange
- 8021 CCLP** Comfort Clear™, Polished Flange
- 8021 CCL** Comfort Clear™, Molded Trim Ring
- 8021**  Add suffix. See options for other finishes.

### Frame-In Kit

- S6132BU** 6" aperture, 1 lamp 26/32W Triple Tube CFL (120/277V) 4-Pin (Amalgam)
- Standard Dimming Options:
- S6132B**
- CU3** Lightolier PowerSpec 3% Dimming (120/277V)
- J1LD3** Lutron 5% Dimming (120V)
- J2LD3** Lutron 5% Dimming (277V)
- JUM7** Mark 7 Dimming (120/277V)
- J1MX** Mark 10 Dimming (120V)
- J2MX** Mark 10 Dimming (277V)
- Other dimming product available, please consult factory

### Remodeler Frame-In Kits

- 6126BURM** 6" aperture, 1 lamp 26W Triple Tube CFL (120/277V) 4-Pin (Amalgam)
- 6132BURM** 6" aperture, 1 lamp 26/32W Triple Tube CFL (120/277V) 4-Pin (Amalgam)

### Features

- 1. Reflector:** 16 ga. Alzak® aluminum, 50° visual cutoff to lamp and lamp image, medium distribution. Comfort Clear™ low iridescence finish. Self-flanged or flangeless with molded white trim ring (field paintable).
- 2. Socket Cup:** Effectively dissipates heat and positions lamp holder. Snaps onto reflector neck to assure consistently correct optical alignment without tools.
- 3. Mounting Frame:** Galvanized steel for dry or plaster ceilings. Accepts other 6" Triple Tube reflectors (see S6132BU Spec Sheet).
- 4. Retaining Springs:** Precision-tooled steel friction springs secure reflector to mounting frame for quick, tool-less installation.
- 5. Mounting Brackets:** 16 ga. steel. Adjust from inside of fixture. Use 3/4" or 1 1/2" lathing channel, 1/2" EMT, or optional mounting bars.
- 6. Ballast/J-Box:** Electronic 120V-277V. UL listed for through branch circuit wiring with max of (8) No. 12 AWG, 90°C supply conductors. Outboard mounted to reduce heat transfer and maintain lamp efficacy and life. Service from below without tools.

### Electrical

**Note:** For ballast electrical data and latest lamp/ballast compatibility refer to "Ballast" specification sheet for complete electrical data.  
UL Listed for through branch circuit wiring with max of (8) No 12 AWG, 90 degree C supply conductors.

### Options and Accessories

Comfort Clear™ Finishes <sup>1</sup>		Other Finishes	
Diffuse	<b>CCD</b>	White	<b>WH</b>
Champagne Bronze	<b>CCZ</b>	Specular Clear	<b>CL</b>
Multigroove	<b>MG</b>		

<sup>1</sup>Specify desired flange. **W** White, **P** Polished, Blank - Molded Ring

### Options and Accessories (continued)

- Emergency Ltg. Kit **FA EM3E\***
- FA EM4\***
- Fuse (Slow Blow) Add suffix **F**
- Existing/Thk. Ceiling **FA EC6\***
- Emergency Add suffix **EM\***
- Chicago Plenum Use S6132BULC
- \*See Spec. Sheets: FAEM, FAEC

Mounting Bars & Accessories; see Specification Sheet MBA.  
Sloped Ceiling Adapters; see Specification Sheet SCA.  
IC Frame available; see **C6CFL32** Specification Sheet.

### Labels

UL Listed for damp locations.

Alzak® is a registered trademark of ALCOA.

**US Patent Pending.**

Job Information	Type:
<b>Job Name:</b>	
<b>Cat. No.:</b>	
<b>Lamp(s):</b>	
<b>Notes:</b>	

